

# SAFETY DATA SHEET

## Barrier Cream

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

#### Trade Name - Barrier Cream

Supplier: Chemical Solutions  
42 Kennel Lane  
Fetcham  
Surrey KT22 9PJ  
0870 2408893

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Conc. CAS EINECS Risks  
Butane 1-10% 106-97-8 203-448-7 F+;R12

### 3. HAZARDS IDENTIFICATION

Most important hazards Extremely flammable.

### 4. FIRST AID MEASURES

**Skin contact.** May cause skin irritation in susceptible persons. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

In the case of skin irritation or allergic reactions see a physician.

**Eye contact.** May cause eye irritation of susceptible persons. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

**Inhalation.** Inhalation of vapours is irritating to the respiratory system, may cause throat pain and cough. Move to fresh air. Consult a physician after significant exposure.

**Ingestion.** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Consult a physician if necessary.

General advice In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
Print Date 21-Oct-2005

### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO<sub>2</sub>). Alcohol-resistant foam.

**Specific hazards.** Extremely flammable. Flash back possible over considerable distance. Vapours may form explosive mixture with air.

#### **Special protective equipment for firefighters**

Wear self contained breathing apparatus for fire fighting if necessary.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **Personal precautions**

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Use personal protective equipment.

#### **Environmental precautions**

Do not let product enter drains. Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up.** Soak up with inert absorbent material and dispose of as hazardous waste. After cleaning, flush away traces with water.

### **7. HANDLING AND STORAGE**

**Handling.** Avoid contact with skin and eyes. Ensure adequate ventilation or exhaust ventilation in the working area. Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from sources of ignition - No smoking.

#### **Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. Keep away from food, drink and animal feeding stuffs.

### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure limit(s)

Butane WEL 8-hr limit ppm: 600

WEL 15 min limit ppm: 750

WEL 8-hr limit mg/m<sup>3</sup>: 1450

WEL 15 min limit mg/m<sup>3</sup>: 1810

Engineering measures Ensure adequate ventilation, especially in confined areas.

Respiratory protection Wear self contained breathing apparatus for fire fighting if necessary.

Hand protection PVC or other plastic material gloves.

Eye protection Goggles.

Skin and body protection Wear chemical protective clothing.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Description Aerosol.

Colour Off-white.

Flash point -20°C

Print Date 21-Oct-2005

## **10. STABILITY AND REACTIVITY**

Stability Stable under normal conditions.

**Conditions to avoid** Heat, flames and sparks.

**Materials to avoid** Incompatible with oxidising agents.

## **11. TOXICOLOGICAL INFORMATION**

Acute toxicity No data is available on the product itself.

## **12. ECOLOGICAL INFORMATION**

Ecotoxicity effects No data is available on the product itself.

## **13. DISPOSAL CONSIDERATIONS**

General Information Dispose of in accordance with local regulations.

## **14. TRANSPORT INFORMATION**

ADR/RID

UN-No 1950 Packing group -

Class 2 Hazard ID -

Proper shipping name AEROSOLS

IMDG-Code

UN-No 1950 Packing group -

Class 2 Marine pollutant .

EmS F-D S-U

IATA-DGR

UN-No 1950 Packing group -

Class 2 Sub-risks see SP63

## **15. REGULATORY INFORMATION**

**Labelling** The product is classified and labelled in accordance with Directive 1999/45/EC.

The product is classified in accordance with Annex VI to Directive 67/548/EEC.

Symbol(s): F+ - Extremely flammable

R-phrases R12 - Extremely flammable.

S-phrases S 2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S25 - Avoid contact with the eyes.  
S51 - Use only in well ventilated areas.  
Print Date 21-Oct-2005

## **16. OTHER INFORMATION**

Text of R phrases  
mentioned in Section 2  
R12 - Extremely flammable.

### **Further information**

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process,.  
Print Date 21-Oct-2005

