

SAFETY DATA SHEET
Lemon Dashboard Renovator

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product Name. Lemon Dashboard Renovator

Company
Chemical Solutions
42 Kennel Lane
Fetcham
Surrey
KT22 9PJ

0870 240 8893

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

Conc. CAS EINECS Risks

Para-mentha-1,4 (8) -Diene 0-0.5% 586-62-9 209-578-0 R10 N;R51/53 Xn;R65

Naphtha (petroleum), Hydrotreated Light 30-40% 64742-49-0 265-151-9 F;R11 Xi;R38
N;R51/53 Xn;R65 R67 Butane 10-20% 106-97-8 203-448-7 F+; R12

3. HAZARDS IDENTIFICATION

Main hazards Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

Skin contact Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact. Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation. Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion. Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon dioxide (CO2).

Fire hazards. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

Protective equipment Self-contained breathing apparatus. Wear protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions. Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods. Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

Storage. Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits.

Butane WEL 8-hr limit ppm: 600

WEL 15 min limit ppm: 750

WEL 8-hr limit mg/m³: 1450

WEL 15 min limit mg/m³: 1810

Engineering measures. Ensure adequate ventilation of the working area.

Respiratory protection. Wear suitable respiratory equipment when necessary.

Hand protection. Chemical resistant gloves (PVC).

Eye protection. Approved safety goggles.

Protective equipment. Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid.

Colour Colourless.

Odour Pleasant.

Flash point -20°C

10. STABILITY AND REACTIVITY

Stability. Stable under normal conditions.

Conditions to avoid. Heat, sparks and open flames.

Materials to avoid. Oxidising agents.

11. TOXICOLOGICAL INFORMATION

Toxicological information

No data is available on this product.

Acute toxicity. No data is available on this product.

12. ECOLOGICAL INFORMATION

Ecotoxicity. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

General information. Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID

UN 1950 Packing group - Class 2

Hazard ID -
Proper Shipping
Name
AEROSOLS
IMDG
UN 1950 Packing group -
Class 2 Marine pollutant .
EmS Code F-D S-U
IATA
UN 1950 Packing group -
Class 2 Subsidiary risk see SP63

15. REGULATORY INFORMATION

Labelling. The product is classified in accordance with 67/548/EEC.
Symbols F+ - Extremely flammable; Xi - Irritant; N - Dangerous for the environment

Risk phrases.

R12 - Extremely flammable.

R38 - Irritating to skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

Safety phrases

S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S24/25 - Avoid contact with skin and eyes.

S29 - Do not empty into drains.

S37 - Wear suitable gloves.

S51 - Use only in well-ventilated areas.

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.

16. OTHER INFORMATION

Text of risk phrases in Section 2

R10 - Flammable.

R11 - Highly flammable.

R12 - Extremely flammable.

R38 - Irritating to skin.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 - Harmful: may cause lung damage if swallowed.

R67 - Vapours may cause drowsiness and dizziness.

Further information.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product.

This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.